


ITX-HW365 VER:1.0



Mode No.	ITX-HW365 VER:1.0
Processor	Support LGA1151 6 th /7 th /8 th /9 th Intel® Celeron/Pentium/Core™ i3/i5/i7 processor Note: supports 6th/7th 95W, 8th/9th only support: 6 core 95W and below CPU, 8 core 35W CPU
Chipset	Adopt Intel® B365 High speed chipset
Memory	2* DDR4 SODIMM memory slot, supports 2400/2133MHz memory, is up to 32GB
Display	Integrated Intel® HD Graphics, supports DirectX12,OpenGL4.4, supports 4K display 1* HDMI1.4, the maximum resolution supported is: 4096X2304@24Hz 1* Display port ,the maximum resolution supported is: 4096X2304@60Hz 1* LVDS, supports dual channels 24BIT
Ethernet	1* RTL8111H Gigabit Ethernet, supports Wake on LAN/PXE function
Storage	2* SATA3.0, the transfer rate is up to 6Gbps
	1* M.2 slot , supports M.2 2280/2260/2240 PCIe4/SATA SSD,PCIe/SATA Automatic Identification
Audio	Onboard ALC662 6 channel high fidelity audio controller, supports MIC/Line-out and power amplifier Supports power amplifier 2Ω/5W dual channels
Expansion Slot	1* M.2 slot, supports M,2 2230 WIFI module
Rear I/O interface	1* HDMI
	1* HDMI - IN, supports external HDMI Signal input and automatically switch to LVDS output (need to enter LVDS screen FW)
	1* Display port
	4* USB3.0
	1* RJ45 Gigabit Network Interface
	1* Line-out (Green), 1*MIC (Red)
	1* DC12~19V power input interface
Built in I/O interface	1* LVDS, 2*15pin, supports dual channels 24BIT
	1* Backlight power supply interface, 1*6pin
	4* USB2.0, 2*5pin
	2* USB3.0 ,2*10pin
	1* TPM, 2*10pin
	2* Hard disk power supply interface, 1*4pin
	1* RS232 COM, 2*5pin
	1* Front audio interface, 2*5pin
	1* Power interface, 1*4pin
	1* 4pin ATX power interface, supports 12V~19V power input output
	1* Front panel function button and indicator light interface, 2*5pin

Fan Connector	1*4pin CPU smart fan connector, 1*3pin system smart fan connector
GPIO	Support 4-way input output GPIO function
BIOS	128Mb Flash ROM
OS	Windows® 7/ 8.1/ 10
Watchdog	Support hardware reset function (L256, 0~255 seconds)
Power Type	Support DC12V~19V power supply
Working temperature	-10°C ~ 60°C
Storage temperature	-20°C ~ 70°C
Working Humidity	5%-95%(relative humidity, non-condensing)
Dimension	170mm x 170mm

Order information:

No.	Model	Processor	Frequency	South bridge	Memory	HDMI	DP	LVDS	LAN	USB	COM	RS485/422	Power
1	ITX-HW365 VER:1.0	LGA1151	/	B365	2*SODDDR4	1	1	2ch/24bit	1*8111H	10	1	/	DC12~19V