


ITX-B330_I526L VER:1.0

(3210M)



Model No.	ITX-B330_I526L VER:1.0(3210M)
Processor	Integrated Intel®Core I5-3210M /2.5GHz Dual core Quad thread CPU,TDP 18W
	Compatible with Intel® Sandy /Ivy Bridge Celeron/Pentium/I3/I5/I7 BGA1023 low power processor
Chipset	Intel® HM76 high speed chipset
Memory	1*SODDDR3 memory slot, supports DDR3 c memory, up to 8GB
Display	Integrated Intel® HD Graphics4000, supports independent display, dual display mode, extended mode
	1*VGA, 2*HDMI,1* LVDS, supports dual channels 24bit, share pin with EDP
Ethernet	2* RTL8111H Gigabit Ethernet , supports Wake on LAN/PXE function
Storage	2* SATA 2.0, the transfer rate is up to 3Gbps
	1*MSATA slot, supports SSD, the transfer rate is up to 6Gbps
Audio	Onboard ALC262 6 channel high fidelity audio controller, supporting MIC,Line-out and power amplifier
	Suggest power amplifier 4Ω3W horn
Expansion Slot	1* Mini-PCIE, supports WIFI 3G/4G module
Rear I/O interface	2* USB 3.0
	1* HDMI
	1* VGA
	2* RJ-45 Gigabit Network Interface
	1* Line out (Green)
	1* Mic (Red)
	1* 12V DC_JACK input
Built in I/O interface	1* LVDS (2*15pin), supports dual channels 24bit (dual 8)
	1* LVDS backlight interface (1*6pin)
	1* J_HDMI (2*8Pin)
	1* JVGA1 (1*12pin) (Same signal as DB15)
	6* RS232 (COM2/3 support RS422/485, COM1/COM2 supports the 9 th pin charged)
	1* LPT (2*13pin)
	8* USB 2.0 (2*5pin),
	1* PS/2 keyboard and mouse interface (1*6Pin)
	1* Front panel function button and indicator light interface (2*5pin)
	1* Front audio interface (2*5pin)
	1* Power amplifier interface (1*4pin)

	1* SIM card slot
	2* Hard disk power supply interface (1*4pin)
	1* 4pin DC power interface, supports 12V power input output
Fan Connector	1* 4pin CPU smart fan connector, 1*4pin system fan connector
GPIO	Support 4-way input output GPIO function
BIOS	32Mb Flash ROM
Watchdog	Support hardware reset function (L256, 0~255 seconds)
OS	Window 7/Windows 10/Linux
Power Type	DC 12V
Working temperature	-10℃～60℃
Storage temperature	-20℃～70℃
Working Humidity	5%-95%(relative humidity, non-condensing)
Dimension	170mm x 170mm

Order information:

No.	Model	CPU	PCH	Frequency	Memory	VGA	HDMI	LVDS	LAN	USB	COM	485/422	Power
1	ITX-B330_I516L VER:1.0(3210M)	I5-3210M	HM76	2.5G	1*SODDDR3	1	2	2*24BIT	1*8111H	10	6	COM2/3	DC12V
2	ITX-B330_I516L VER:1.0(3317U)	I5-3317U	HM67	2.5G	1*SODDDR3	1	2	2*24BIT	1*8111H	10	6	COM2/3	DC12V
3	ITX-B330_I526L VER:1.0(3210M)	I5-3210M	HM76	2.5G	1*SODDDR3	1	2	2*24BIT	1*8111H	10	6	COM2/3	DC12V